

MOTIP Anti-Welding Spray

Ord.-no.: 090404

Technical Information



Prevent adhesion of welding splatter to the area around the welding zone with MOTIP Anti-Welding. It is non-flammable, silicone-free, and non-corrosive. Anti-Welding offers great coverage, can be removed with water and has a misty spray pattern.

Quality & properties

- Can be removed with water
- Misty spray pattern
- Silicone-free
- Non-flammable
- Slightly basic
- Non-corrosive
- 360° valve

Physical & chemical data

- Base: Emulsifying oil
- Colourname: Transparent white
- Surfaces: Welding guns, Welding zones
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 2,7
- Vapour pressure: 8500/20 bar
- Flash point: >100 °C
- Relative density: 1 g/ml
- Storage stability: 10 years
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Best processing temperature 5 to 35°C.
- Before use, shake the aerosol.
- Spray the parts to be protected and execute the welding.
- Remove welding spatter with a steel brush.
- If desired, remove oil with water or a moist cloth.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 24, 2021 – This release replaces all eventually earlier issued versions.