2 - PRODUCT DATA SHEET V200430

P5R Core

PRODUCT DESCRIPTION

The P5R Core is lightweight (75 g) and extremely compact, so it fits comfortably in the pocket of a jacket or trouser. Despite its compact size, it packs a powerful light punch, is extremely weather-resistant and equipped with the latest light technologies. Light functions can be customized to the user more easily than ever before with the Smart Light Technology. The Magnetic Charge System provides easy charging of the battery and thanks to the Flex Sealing Technology, the lamp can easily handle permanent submersion in water.

- Advanced Focus System for efficient, precise flood and spot lighting
- Smart Light Technology for custom light functions
- High protection against dust and water (IP68) through Flex Sealing Technology
- Constant Light for constant luminous flux over a long period of time
- Convenient charging of the battery with Magnetic Charge System

TECHNICAL DATA			
Length defocused [mm]	123		
Length focused [mm]	127		
Head diameter [mm]	29		
Tube diameter [mm]	22		
Weight incl. batteries [g]	106		
Weight without batteries [g]	85		
Focus function	Yes		
Head material	Aluminum alloy		
Tube material	Aluminum alloy		
Optic	Plastic lense (PMMA)		
Cartridge	No		

POWER SUPPLY				
Power source type	Rechargeable battery			
Battery quantity	1			
Battery type	Li-ion			
Battery replaceable	Yes			
Total battery voltage [V]	3.7			
Total battery capacity [mAh]	750			
Total battery energy ² [Wh]	2.77			
Rechargeable	Yes			
Charging time ⁵ [min]	120			
Energy modes	Constant Light			
Energy status indicator	Battery Indicator,			
	Charge Indicator,			
	Low Battery Warning			

FURTHER SPECIFICATI	ONS
IP class	IP68
Drop test (drop height) [m]	2
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Boost, Low Power, Mid Power, Power, Position, Blink, S.O.S., Strobe

LIGHT SOURCE			
Amount LEDs	1		
LED type	High Power LED		
Color	White		
Color temperature [K]	6000 to 7500		
Color rendering index (CRI)	70		

LIGHT VALUES	5			
ANSI – Constant Light	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]	500	350	130	15
Beam distance ¹ [m]	250	180	110	40
Run time ¹ [h]		1	3.5	25

SWITCH

Front Switch

FEATURES

 $\label{eq:def:Dimmable} \mbox{Dimmable , Transportation lock , Flicker Free, Memory Function, Back-Up Light}$

TECHNOLOGIES

Advanced Focus System³, Smart Light Technology, Magnetic Charge System, Emergency Light, Temperature Control System, Flex Sealing Technology

