

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: PROMASTOP®-M
UFI	: Y71S-EM2J-M40E-RJ4C
Type of product	: Solid, dry powder.
Product group	: Fire stopping mortar

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Etex France Building Performance S.A.
3 Route de Claye
FR 77181 Le Pin
FRANCE
T +33 (0)160 26 64 00
www.siniat.fr

Other

Etex Building Performance GmbH
St.-Peter-Straße 25
AT 4021 Linz
AUSTRIA
T +43 732 6912 0
info.at@etexgroup.com, www.promat.at

Other

Etex Building Performance S.p.A.
Via Perlasca 14
IT 27010 Vellezzo Bellini (PV)
ITALY
T +39 0382 4575 251, F +39 0382 4575 250
info@promat.it, www.promat.it

Other

Etex Poland sp. z o.o.
ul. Przeclawska 8
PL 03-879 Warszawa
POLAND
T +48-22 212 2280
top@promatop.pl, www.promat.com

Other

Etex France Building Performance S.A.
500 rue Marcel Demonque, Agroparc - CS70088
FR 84915 Avignon Cedex 9
FRANCE
T +33 (0)432 44 44 44
fds.efbp@etexgroup.com, www.promat.fr

Other

Other

Etex Building Performance N.V.
Bormstraat 24
BE 2830 Tiselt
BELGIUM
T +32 15 71 81 00, F +32 15 71 81 09
info@promat-international.com, www.promat-international.com

Other

Etex Building Performance Limited
Gordano House, Marsh Lane, Easton-in-Gordano
Eastern Road
GB BS20 0NE Bristol, Berkshire
UNITED KINGDOM
T +44 (0800) 373 636
marketinguk@promat.co.uk, www.promat.co.uk

Other

Promat UK Limited Ltd
B1 The Innovation Centre, Pilsworth Road - Heywood Distribution Park
Pilsworth Road
GB OL10 2TS Heywood
UNITED KINGDOM
T +44 (0)800 588 4444
sales@promat.co.uk

Other

Promat s.r.o.
Evropská 11/2758
CZ 16000 Praha 6 - Dejvice
CZECH REPUBLIC
T +420 224 390 811
promat.praha@etexgroup.com, www.promatpraha.cz

Other

Etex Nordic A/S
Vendersgade 74,3
DK 7000 Fredericia
DENMARK
T +45 7366 1999
Promat-dk@etexgroup.com, www.promat.com/da-dk

Other

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Promat Ibérica S.A.
C/ Velazquez, 47 – 6° Izquierda
ES 28001 Madrid
SPAIN
T +34 91 781 1550, F +34 91 575 15 97
info@promat.es, www.promat.es

Other

Promat d.o.o.
Trata 50
SI 4220 Skofja Loka
SLOVENIA
T +386 4 51 51 451, F +386 4 51 51 450
info@promat-see.com, www.promat-see.com

Other

Etex Middle East LLC
Plot No. 597-921 Dubai Investment Park 2
AE 123945 Dubai
UNITED ARAB EMIRATES
T +971 4 885 3070, F +971 4 885 3588
info@promatfp.ae, www.promat.com

Etex Building Performance GmbH
Scheifenkamp 16
DE 40878 Ratingen
GERMANY
T +49 (0)2102 493 0, F +49 (0)2102 493 111
mail@promat.de, www.promat.de

Other

Promat AG
Industriestrasse 3
CH 9542 Münchwilen
SWITZERLAND
T +41 52 320 9400, F +41 52 320 9402
office@promat.ch, www.promat.ch

1.4. Emergency telephone number

Emergency number : Please contact a regional poison center or emergency telephone number.

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	112 +356 2545 6508	
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation H335

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05

GHS07

Signal word (CLP)

: Danger

Contains

: Portland cement; Flue dust Portland cement

Hazard statements (CLP)

: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Precautionary statements (CLP)

: P261 - Avoid breathing dust.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 - Dispose of contents and container to an approved waste disposal plant.

Extra phrases

: Skin contact with wet cement, fresh concrete or mortar may cause irritation, dermatitis or burns. May cause damage to products made of aluminium or other non-noble metals.

2.3. Other hazards

Other hazards which do not result in classification

: Depending upon the source of the Portland cement, the product could be contaminated with chromium VI. - In several countries, the soluble chromium VI is legally limited to 0.0002% of the total dry weight. If soluble chromium VI is present in the Portland cement above the 0.0002%, a reduction agent has been added to it to keep the content of soluble chromium VI under the 0,0002%. The activity of this reduction agent is limited in time, what limits the shelf life of the product. The product should be used within 1 year after its production date. Natural contamination of some substances of the mixture with crystalline silica could occur. The inhalation of quartz containing dust, in particular the fine dust fraction(respirable size), in high concentrations or over repeated or prolonged periods of time can be hazardous to health and may lead to chronic lung disease and an increased risk of lung cancer. This risk will be minimal if correct working practices are observed and applied. (Refer to Section 8). According to the International Agency for Research on Cancer (IARC Monograph Volume 100C - 2012) "Crystalline silica inhaled in the form of quartz or cristobalite is carcinogenic to humans(Group 1).".

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Calciumcarbonate (471-34-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Calciumcarbonate (471-34-1)	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Portland cement	CAS-No.: 65997-15-1 EC-No.: 266-043-4 REACH-no: 02-2119682167-31	2 – 70	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Fly ashes	CAS-No.: 68131-74-8 EC-No.: 268-627-4 REACH-no: 01-2119491179-27	1 – 10	Eye Irrit. 2, H319
Calciumcarbonate substance with national workplace exposure limit(s) (GB)	CAS-No.: 471-34-1 EC-No.: 207-439-9	10 - 20	Not classified
MICA substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 12001-26-2	10 - 20	Not classified
Flue dust Portland cement	CAS-No.: 68475-76-3 EC-No.: 270-659-9 REACH-no: 01-2119486767-17	1 – 10	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335
Crystalline Silica, respirable fraction substance with national workplace exposure limit(s) (IE); substance with a Community workplace exposure limit	CAS-No.: 14808-60-7 EC-No.: 238-878-4	0 – 0,5	STOT RE 1, H372

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In case of allergy, inflammation or irritation, seek medical advise.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Rinse throat with water and blow nose to evacuate dust. If nose or airways become inflamed, seek medical advice.
First-aid measures after skin contact	: Remove all dust as much as possible. Take off contaminated clothing. Immediately rinse with plenty of water. If skin irritation occurs: Get medical advice/attention. In case of allergy, seek medical advise.
First-aid measures after eye contact	: Do not rub the eye. Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Cement dust may irritate the throat and respiratory tract. Coughing, sneezing, and shortness of breath may occur following exposures in excess of occupational exposure limits.
-----------------------------------	---

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Symptoms/effects after skin contact	: When moistened by water or sweat, the Portland cement component may lead to skin inflammation, contact dermatitis or even delayed onset burns due to high alkalinity. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: All extinguishing media can be used.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire	: Product is not explosive. The product is non-combustible.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid dust formation. Avoid breathing dust. Avoid eye and skin contact. See sections 7 and 8.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Dampen down any dust or use vacuum cleaner with correct filter.
Measures in case of dust release	: Prevent spread of dust.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Do not allow product to spread into the environment. Do not allow entry to drains, sewers, water courses or soil.

6.3. Methods and material for containment and cleaning up

For containment	: Use closed containers to avoid dust release.
Methods for cleaning up	: Minimise generation of dust. Do not use compressed air for cleaning. Do not dry sweep. Dampen down any dust or use vacuum cleaner with correct filter.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See sections 7, 8 and 11.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid dust formation. Do not breathe dust. Avoid contact with skin and eyes. Ensure prompt removal from eyes, skin and clothing. Wear personal protective equipment. Use always respiratory protective equipment when exposures are likely or can be foreseen to exceed the Occupational Exposure Limits or Workplace Exposure Limits in UK (refer to local regulations).
-------------------------------	---

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Handling temperature	: 5 – 45 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in dry, covered and frost proof area. Protect from moisture. Keep away from food, drink and animal feeding stuffs.
Incompatible materials	: Avoid contact with aluminium.
Maximum storage period	: 12 months The packaging is marked with the packing date, the storage conditions and the storage period appropriate to maintain the activity of the reducing agent and to keep the content of soluble chromium VI below the limit indicated in section 2.
Storage temperature	: 5 – 45 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

PROMASTOP®-M	
Ireland - Occupational Exposure Limits	
Assessed dust without specific effect (other particles, not classified anywhere else) (inhalable dust)	10 mg/m ³
Assessed dust without specific effect (other particles, not classified anywhere else) (respirable dust)	4 mg/m ³
United Kingdom - Occupational Exposure Limits	
Assessed dust without specific effect (other particles, not classified anywhere else) (inhalable dust)	10 mg/m ³
Assessed dust without specific effect (other particles, not classified anywhere else) (respirable dust)	4 mg/m ³
Crystalline Silica, respirable fraction (14808-60-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Silica crystalline (Quartz)
IOEL TWA	0.05 mg/m ³ (respirable dust)
Remark	(Year of adoption 2003)
Regulatory reference	SCOEL Recommendations
Ireland - Occupational Exposure Limits	
Local name	Quartz, respirable dust
OEL TWA	0.1 mg/m ³
Remark	BOELV (Binding Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
MICA (12001-26-2)	
Ireland - Occupational Exposure Limits	
Local name	Mica

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

MICA (12001-26-2)	
OEL TWA	3 mg/m ³ R (Respirable Fraction)
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	Mica
WEL TWA (OEL TWA)	0.8 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Calciumcarbonate (471-34-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Calcium carbonate (Limestone, Marble)
WEL TWA (OEL TWA)	10 mg/m ³ total inhalable 4 mg/m ³ respirable
WEL STEL (OEL STEL)	4 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide appropriate exhaust ventilation at places of dust forming.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses with side shields. Use splash goggles when eye contact due to splashing is possible. Foresee eye cleaning on the workplace.

8.2.2.2. Skin protection

Skin and body protection:

Use loose work clothes with closed sleeves. Preventive skin protection creams can be used, but not after skin contact with the product.

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. . Please observe the glove supplier's specifications regarding permeability and breakthrough time. Use alkali resistant gloves.

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	1,1		EN ISO 374-1

8.2.2.3. Respiratory protection

Respiratory protection:

Use appropriate respiratory equipment when exposures are likely or can be foreseen to exceed the Occupational Exposure Limits or Workplace Exposure Limits for the UK (e.g. for exposures up to 10 times the OEL (WEL) use at least a P2 type dust mask. For higher exposure, use a P3 type mask).

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Grey.
Appearance	: Powder.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not applicable
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: Not available
pH solution	: 11 – 13.5
Viscosity, kinematic	: Not applicable
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not applicable
Particle size	: Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Percent Solids : 100 %

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Reacts alkaline with water. A proposed reaction takes place in contact with water, during which the product hardens and forms a solid mass, which does not react with the environment.

10.2. Chemical stability

Stable under normal conditions. Shelf life is maximum 12 months.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Humidity during storage.

10.5. Incompatible materials

Reacts exothermically with acids. The wet product is alkaline and reacts with acids, ammonium salts and base metals e.g. aluminum, zinc or brass. The reaction with base metals produces hydrogen.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Portland cement (65997-15-1)	
LD50 oral	> 2000 mg/kg mouse
LD50 dermal rabbit	> 2000 mg/kg LD0 : 2000 mg/kg
Blast furnace slag (65996-69-2)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 4000 mg/kg
LC50 Inhalation - Rat	> 5.235 g/m ³

Skin corrosion/irritation : Cement powder or a mixture of cement with water can cause irritant contact dermatitis, and/or delayed onset of skin burns. These burns can be very serious in prolonged contact with skin.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Additional information : May cause sensitisation of susceptible persons by skin contact

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Crystalline Silica, respirable fraction (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
Portland cement (65997-15-1)	
STOT-single exposure	May cause respiratory irritation.

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Flue dust Portland cement (68475-76-3)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified

Crystalline Silica, respirable fraction (14808-60-7)

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Inhaling cement dust may aggravate existing respiratory system disease(s) and/or medical conditions such as emphysema or asthma and/or existing skin and/or eye conditions.

Other information : No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation. The fibres used in this product do not meet the definition of critical or respirable fibre as defined by WHO convention because of their large diameter. Because the fibres are considered as non-respirable, they are not expected to pose a cancer risk.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Blast furnace slag (65996-69-2)

LC50 - Fish [1] : > 100 g/l

EC50 - Crustacea [1] : > 90 g/l

EC50 72h - Algae [1] : > 100000 mg/l

12.2. Persistence and degradability

PROMASTOP®-M

Persistence and degradability : Not readily biodegradable.

12.3. Bioaccumulative potential

PROMASTOP®-M

Bioaccumulative potential : Not expected to bioaccumulate.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

Calcium carbonate (471-34-1) : This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Accidental spillage of cement powder in waste water, results in a low increase in the pH. Hydrated cement is a stable material that definitely sets its compounds and makes them insoluble. Do not allow entry to drains, sewers, water courses or soil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : The uncured product must be handled as hazardous waste. In case of disposal, harden with water. Dispose the hardened product as concrete waste.

European List of Waste (LoW, EC 2000/532) : 10 13 14 - waste concrete and concrete sludge
16 03 03* - inorganic wastes containing dangerous substances
17 01 01 - concrete
17 09 04 - mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03
15 01 01 - paper and cardboard packaging

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : Not regulated.
UN-No. (IMDG) : Not regulated.
UN-No. (IATA) : Not regulated.
UN-No. (ADN) : Not regulated.
UN-No. (RID) : Not regulated.

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not regulated.
Proper Shipping Name (IMDG) : Not regulated.
Proper Shipping Name (IATA) : Not regulated.
Proper Shipping Name (ADN) : Not regulated.
Proper Shipping Name (RID) : Not regulated.

14.3. Transport hazard class(es)

ADR
Transport hazard class(es) (ADR) : Not regulated.

IMDG
Transport hazard class(es) (IMDG) : Not regulated.

IATA
Transport hazard class(es) (IATA) : Not regulated.

ADN
Transport hazard class(es) (ADN) : Not regulated.

RID
Transport hazard class(es) (RID) : Not regulated.

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.4. Packing group

Packing group (ADR)	: Not regulated.
Packing group (IMDG)	: Not regulated.
Packing group (IATA)	: Not regulated.
Packing group (ADN)	: Not regulated.
Packing group (RID)	: Not regulated.

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

Overland transport

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

Inland waterway transport

Not regulated.

Rail transport

Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations	: REGULATION (EC) n° 1907/2006 - REACH - Annex XVII, RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES, 47: 1.- Cement and cement-containing preparations shall not be used or placed on the market, if they contain, when hydrated, more than 0,0002 % soluble chromium VI of the total dry weight of the cement. 2.- If reducing agents are used the packaging of cement or cement-containing preparations shall be legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.
--	--

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list.

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

PROMASTOP®-M

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes:

1.3. Details of the supplier of the safety data sheet. 2.2. Label elements. 2.3. Other hazards. 3.2. Mixtures. 8. Exposure controls/personal protection. 15. Regulatory information.

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method

Safety Data Sheet applicable for regions : IE;MT;GB